

Material Safety Data Sheet

May be used to comply with OSHA's Hazard Communication Standard, 29 CFR 1910.1200. Standard must be consulted for specific requirements.

U.S. Department of Labor

Occupational Safety and Health Administration
(Non-mandatory Form)
Form Approved
OMB No. 1218-0072

IDENTITY <i>(As used on label and list)</i> Polyethylene High Density	Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.
--	---

Section I

Manufacturer's Name KING PLASTIC CORPORATION	Emergency Telephone Number 941-493-5502
Address <i>(Number, Street, City, State and ZIP Code)</i> 1100 N. Toledo Blade Blvd.	Telephone Number for Information 941-493-5502
North Port, FL 34288-8694	Date Prepared 12-27-01
	Signature of Preparer <i>(optional)</i>

Section II – Hazardous Ingredients/Identity Information

Hazardous Components <i>(Specific chemical identity; common name(s))</i>	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
None, other than nuisance dust	15 mg/m ³	10mg/m ³ (total dust)	None	None

Section III – Physical/Chemical Characteristics

Boiling Point	Non-volatile	Specific Gravity (H ₂ O = 1)	.941-.965
Vapor Pressure (mm Hg.)	Non-volatile	Melting Point	Non-volatile
Vapor Density (AIR = 1)	Non-volatile	Evaporation Rate (Butyl Acetate = 1)	Non-volatile
Solubility in Water Insoluble.			
Appearance and Odor Translucent, odorless.			

Section IV – Fire and Explosion Hazard Data

Flash Point <i>(Method Used)</i> N/A	Flammable Limits Non-volatile	LEL	UEL
Extinguishing Media Carbon dioxide, water spray, foam or dry chemical.			
Special Fire Fighting Procedures None.			
Unusual Fire and Explosion Hazards Refer to National Fire Protection Association Bulletin 654, "Dust Explosion Prevention, Plastic Industry 1975", for safe handling procedures.			

(Reproduce locally)

OSHA 174. Sept. 1985

Section V – Reactivity Data

Stability	Unstable		Conditions to Avoid
	Stable	X	
Incompatibility (<i>Materials to Avoid</i>) Attacked by oxidizing agents such as nitric or perchloric acid and free halogens. Also softened by hydrocarbons such as benzene, gasoline, lubricating oils, petroleum ether and by chlorinated hydrocarbons.			
Hazardous Decomposition or Byproducts Burning yields CO and CO ² .			
Hazardous Polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

Section VI – Health Hazard Data

Route(s) of Entry:	Inhalation? N/A	Skin? N/A	Ingestion? N/A
Health Hazards (<i>Acute and Chronic</i>) No acute hazard.			
Carcinogenicity:	NTP? N/A	IARC Monographs? N/A	OSHA Regulated? N/A
Signs and Symptoms of Exposure N/A			
Medical Conditions Generally Aggravated by Exposure N/A			
Emergency and First Aid Procedures No acute hazard.			

Section VII – Precautions for Safe Handling and Use

Steps to be Taken in Case Material is Released or Spilled Sweep up and collect as essentially harmless organic wastes.	
Waste Disposal Method Dispose of in accordance with local, state and federal regulations.	
Precautions to be Taken in Handling and Storing No specific requirements.	
Other Precautions Self-contained breathing apparatus for fire fighting personnel is recommended.	

Section VIII – Control Measures

Respiratory Protection (<i>Specific Type</i>) Not generally required.				
Ventilation	Local Exhaust	N/A	Special	N/A
	Mechanical (<i>General</i>)	N/A	Other	Normal working environment.
Protective Gloves Not generally required.			Eye Protection Safety glasses recommended.	
Other Protective Clothing or Equipment Not generally required.				
Work/Hygienic Practices N/A				

USGPO 1986-491-529/45775